AMENDMENTS TO THE CLAIMS:

This listing of the claims will replace all prior versions, and listings, of the claims in this application.

Listing of Claims:

1. (Currently Amended) A method for routing data packets in a wireless network, comprising:

estimating a link bandwidth of at least one network node;

calculating a connectivity metric based on the estimated link bandwidth;

distributing information concerning the calculated connectivity metric using a routing protocol packet; and

using the calculated connectivity metric, determining a route having a maximum link bandwidth and a minimum traffic load.

2. (Original) A method as in claim 1, where estimating uses a model of a network medium access control MAC algorithm.

3. (Original) A method as in claim 1, where estimating uses a model of a Bluetooth network medium access control MAC algorithm.

4. (Currently Amended) A method ~~as in claim 1~~ for routing data packets in a wireless network, comprising:

estimating a link bandwidth of at least one network node;

calculating a connectivity metric based on the estimated link bandwidth;

distributing information concerning the calculated connectivity metric; and

using the calculated connectivity metric, determining a route having a maximum link bandwidth and a minimum traffic load, where said connectivity metric comprises a ratio of a maximum link bandwidth to the estimated link bandwidth, where the maximum link bandwidth is the link bandwidth between a Master node and a Slave node when there is only one Slave node connected to the Master node.

5. (Original) A method as in claim 4, where determining the route comprises:

calculating the connectivity metric of links along a plurality of routes;

determining a maximum connectivity metric value of each of the plurality of routes; and

selecting the route having the smallest connectivity metric value.

6. (Currently Amended) A method ~~as in claim 1~~ for routing data packets in a wireless network, comprising:

estimating a link bandwidth of at least one network node;

calculating a connectivity metric based on the estimated link bandwidth;

distributing information concerning the calculated connectivity metric; and

using the calculated connectivity metric, determining a route having a maximum link bandwidth and a minimum traffic load, where estimating includes considering a node's status and the number of the node's Slaves.

7. (Original) A method as in claim 6, where considering a node's status considers whether a node is a Master node, a Slave node, or a Participant in Multiple Piconet (PMP) node.

8. (Original) A method as in claim 7, where a maximum link bandwidth B_O is the link bandwidth between the Master and Slave nodes, when there is only one Slave node present in a piconet, and where all piconets have the same value of B_o, where M_i is the number of Slave nodes in piconet *i*, and P_i is the number of piconets that a PMP node connects to, and where Bi is the link bandwidth of the Master-Slave link in piconet *i*.and where the connectivity metric B_i/B_o is determined at least in accordance with:

Master →Slave: $$\frac{B_i}{B_0} = \frac{1}{M_i}$$

Slave →Master: $$\frac{B_i}{B_0} = \frac{1}{M_i}$$

$\text{Master}_i \rightarrow$ PMP (S/S) $\rightarrow \text{Master}_j$: $$\frac{B}{B_0} = \frac{1}{P_i} MIN(\frac{B_i}{B_o}, \frac{B_j}{B_o}) = \frac{1}{P_i} MIN(\frac{1}{M_i}, \frac{1}{M_j}),$$

and

$\text{Master}_j \rightarrow \text{PMP}(\text{S}/\text{M}_k) \rightarrow$ Slave: $$\frac{B}{B_o} = MIN(\frac{1}{M_k + 1}, \frac{1}{M_i}).$$

9. (Currently Amended) A method ~~as in claim 1~~ for routing data packets in a wireless network, comprising:

estimating a link bandwidth of at least one network node;

calculating a connectivity metric based on the estimated link bandwidth;

distributing information concerning the calculated connectivity metric; and

using the calculated connectivity metric, determining a route having a maximum link bandwidth and a minimum traffic load, where distributing information concerning the calculated connectivity metric comprises inserting the value of the connectivity metric into a routing protocol packet in place of the value of a hop number.

10. (Currently Amended) A method ~~as in claim 1~~ for routing data packets in a wireless network, comprising:

estimating a link bandwidth of at least one network node;

calculating a connectivity metric based on the estimated link bandwidth;

distributing information concerning the calculated connectivity metric; and

using the calculated connectivity metric, determining a route having a maximum link bandwidth and a minimum traffic load, where distributing information concerning the calculated connectivity metric comprises inserting the value of the connectivity metric into a routing protocol packet in conjunction with the value of a hop number.

11. (Currently Amended) A computer program embodied on a computer readable medium and comprising computer program code segments for use by at least one data processor when implementing a routing protocol in a wireless network, comprising:

a first computer program code segment for estimating the link bandwidth of at least one network node;

a second computer program code segment for calculating a connectivity metric based on the

estimated link bandwidth; ~~and~~

a third computer program code segment that uses the calculated connectivity metric to determine a route having a maximum link bandwidth and a minimum traffic load; and

a further computer program code segment for sending information concerning a calculated connectivity metric to at least one other network node using a routing protocol packet.

12. (Original) A computer program as in claim 11, where said first computer program code segment uses a model of a network media access control algorithm.

13. (Original) A computer program as in claim 11, where said first computer program code segment uses a model of a Bluetooth network media access control algorithm.

14. (Currently Amended) A computer program ~~as in claim 11~~ embodied on a computer readable medium and comprising computer program code segments for use by at least one data processor when implementing a routing protocol in a wireless network, comprising:

a first computer program code segment for estimating the link bandwidth of at least one network node;

a second computer program code segment for calculating a connectivity metric based on the estimated link bandwidth; and

a third computer program code segment that uses the calculated connectivity metric to determine a route having a maximum link bandwidth and a minimum traffic load, where said second computer program code segment calculates said connectivity metric to be a ratio of a maximum link bandwidth to the estimated link bandwidth, where the maximum link bandwidth is the link bandwidth between a Master node and a Slave node when there is only one Slave node in the network.

15. (Original) A computer program as in claim 14, where said third computer program code segment comprises computer program code for calculating the connectivity metric of links along a plurality of routes, for determining a maximum connectivity metric value of each of the plurality of routes and for selecting the route having the smallest connectivity metric value

16. (Currently Amended) A computer program ~~as in claim 11~~ embodied on a computer readable medium and comprising computer program code segments for use by at least one data processor when implementing a routing protocol in a wireless network, comprising:

a first computer program code segment for estimating the link bandwidth of at least one network node;

a second computer program code segment for calculating a connectivity metric based on the estimated link bandwidth; and

a third computer program code segment that uses the calculated connectivity metric to determine a route having a maximum link bandwidth and a minimum traffic load, where said first computer program code segment considerers a node's status and the number of the node's Slaves when estimating the link bandwidth of the node.

17. (Original) A computer program as in claim 16, where considering a node's status considers whether a node is a Master node, a Slave node, or a Participant in Multiple Piconet (PMP) node.

18. (Currently Amended) A computer program ~~as in claim 11~~, embodied on a computer readable medium and comprising computer program code segments for use by at least one data processor when implementing a routing protocol in a wireless network, comprising:

a first computer program code segment for estimating the link bandwidth of at least one network node;

a second computer program code segment for calculating a connectivity metric based on the estimated link bandwidth; and

a third computer program code segment that uses the calculated connectivity metric to determine a route having a maximum link bandwidth and a minimum traffic load, where a maximum link bandwidth B_O is the link bandwidth between the Master and Slave nodes, when there is only one Slave node present in a piconet, and where all piconets have the same value of B_o, where M_i is the number of Slave nodes in piconet *i*, and P_i is the number of piconets that a PMP node connects to, and where Bi is the link bandwidth of the Master-Slave link in piconet *i*, and where the connectivity metric B_i/B_o is determined at least in accordance with:

Master →Slave: $\frac{B_i}{B_0} = \frac{1}{M_i}$

Slave →Master: $\frac{B_i}{B_0} = \frac{1}{M_i}$

$\text{Master}_i \rightarrow \text{PMP (S/S)} \rightarrow \text{Master}_j$: $\frac{B}{B_0} = \frac{1}{P_i} MIN(\frac{B_i}{B_o}, \frac{B_j}{B_o}) = \frac{1}{P_i} MIN(\frac{1}{M_i}, \frac{1}{M_j})$,

and

$\text{Master}_j \rightarrow \text{PMP(S/M}_k) \rightarrow \text{Slave}$: $\frac{B}{B_o} = MIN(\frac{1}{M_k + 1}, \frac{1}{M_i})$.

19. (Currently Amended) A computer program ~~as in claim 11~~ embodied on a computer readable medium and comprising computer program code segments for use by at least one data processor when implementing a routing protocol in a wireless network, comprising:

a first computer program code segment for estimating the link bandwidth of at least one network

node;

a second computer program code segment for calculating a connectivity metric based on the estimated link bandwidth; and

a third computer program code segment that uses the calculated connectivity metric to determine a route having a maximum link bandwidth and a minimum traffic load, where the value of the connectivity metric is inserted into a routing protocol packet in place of the value of a hop number.

20. (Original) A computer program as in claim 11, where the value of the connectivity metric is inserted into a routing protocol packet in conjunction with the value of a hop number.

21. (Original) A computer program as in claim 11, further comprising a computer program code segment for receiving information concerning a calculated connectivity metric from at least one other network node.

22. Cancelled

23. (New) A mobile node comprising means for coupling to a wireless network, further comprising:

means for estimating the link bandwidth of at least one network node;

means for calculating a connectivity metric based on the estimated link bandwidth;

means, responsive to the calculated connectivity metric, for determining a route having a maximum link bandwidth and a minimum traffic load; and

means for sending information concerning the calculated connectivity metric to at least one other

network node using a routing protocol packet.

24. (New) A mobile node as in claim 23, where said estimating means uses a model of a network media access control algorithm.

25. (New) A mobile node as in claim 23, where said estimating means uses a model of a Bluetooth network media access control algorithm.

26. (New) A mobile node as in claim 23, where said calculating means calculates said connectivity metric to be a ratio of a maximum link bandwidth to the estimated link bandwidth, where the maximum link bandwidth is the link bandwidth between a Master node and a Slave node when there is only one Slave node in the network.

27. (New) A digital data storage medium embodying a computer-executable program comprising operations of:

estimating a link bandwidth of at least one network node in a wireless multi-hop network using at least in part a consideration of a number of, and the role played by, other nodes that are coupled to the at least one node, where the role comprises one of a master (M), a slave (S), and a participant in multiple piconet (PMP);

calculating a connectivity metric based on the estimated link bandwidth;

distributing information concerning the calculated connectivity metric; and

using the calculated connectivity metric, determining a route in a load-balanced manner for a packet.

28. A digital data storage medium as in claim 27, where the connectivity metric comprises a ratio of a maximum link bandwidth to the estimated link bandwidth, where the maximum link

bandwidth is the link bandwidth between a Master node and a Slave node when there is only one Slave node connected to the Master node.